




TRIANGLES LED 8141




TRIANGLES LED

Painted aluminum, glass

8143 8142 8141



SINUS 8144



SINUS

Painted aluminum, glass


8144

1xGU10, max 10W only LED

IP54



PATRAS LED 9115




PATRAS LED

Painted aluminum, glass

9115



ELLIPSES LED 8181




ELLIPSES LED

Painted aluminum, glass

8140 8182 8181



MUNO LED 6776



MUNO LED

Painted aluminum, glass

6776



Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
8140	2x5W LED	3000K	800 lm	180°	≥80	~220-230 V, 50/60 Hz	⊕	>0,5	IP54	10000h
8141	2x5W LED	3000K	750 lm	180°	≥80	~220-230 V, 50/60 Hz	⊕	>0,5	IP54	10000h
8142	2x5W LED	3000K	700 lm	180°	≥80	~220-230 V, 50/60 Hz	⊕	>0,5	IP54	10000h
8143	2x5W LED	3000K	800 lm	180°	≥80	~220-230 V, 50/60 Hz	⊕	>0,5	IP54	10000h
8181	2x5W LED	3000K	750 lm	180°	≥80	~220-230 V, 50/60 Hz	⊕	>0,5	IP54	10000h
8182	2x5W LED	3000K	700 lm	180°	≥80	~220-230 V, 50/60 Hz	⊕	>0,5	IP54	10000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9115	4x1W LED	3000K	320 lm	38°	≥80	~220-230 V, 50/60 Hz	⊕	>0,5	IP54	10000h
6776	6W LED	3000K	240 lm	120°	≥80	~220-230 V, 50/60 Hz	⊕	>0,5	IP54	8000h

WHITE BLACK-GOLD BLACK

BLACK GRAPHITE